

REACH TRUCKS

KANGAROO SERIES/HUMANIC SERIES

Model	Capacity (kg)	Max. Lifting Height (mm)
MRT 15 (Stand-On)	1500	6200
MRT KE 14 (SI-Drive)	1600	6000
MRT KE 14 (SI-Drive)	1600	6000
MRT KE 20 (SI-Drive)	2000	6000
MRT HX 25 (SI-Drive)	2500	11500

KANGAROO SERIES



MRT 15
STAND-ON



HUMANIC SERIES



REACH TRUCKS

Model	MRT 15	MRT KE 14	MRT KE 14	MRT KE 20	MRT HX 25
	Kangaroo Series				Humanic Series
Type	Stand-On	SI-Drive	SI-Drive	SI-Drive	SI-Drive
Capacity (kg)	1500	1600	1600	2000	2500
Load Centre (mm)	500	600	600	600	600
Maximum Lifting Height (mm)	6200	6000	6000	6000	11500
Lowered Mast Height (mm)	2640	2810	3010	3310	4678
Extended Mast Height (mm)	7000	6950	6950	6950	12336
Residual Load Value at Mast LH Height (kg)	800	600	700	1000	1000
Overall Width (mm)	1020	1240	1240	1272	1440
Axis Width	2000	2625	2625	2905	2850
Battery (V/Ah)	48 / 400	48 / 400	48 / 500	48 / 500	48 / 500