

**Cold Rolled plate**

Thickness (mm)	Width (mm)
0.30, 0.35	900, 905, 920
0.40, 0.45	900, 905, 920, 1000, 1020
0.5	900, 905, 920, 1000, 1020
0.60	900, 905, 920, 1000, 1020, 1100
0.63	900, 905, 920, 1000, 1020, 1100, 1220, 1250, 1270
0.70	900, 905, 920, 1000, 1020, 1220, 1270
0.8, 0.9	900, 920, 1000, 1020, 1220, 1250, 1270, 1420
1.00	900, 920, 1000, 1020, 1220, 1250, 1270, 1320, 1420, 1520, 1580
1.25, 1.50	900, 920, 1000, 1020, 1220, 1250, 1.60/1.85 1270, 1320, 1420, 1520, 1580, 1620
2.00	900, 920, 1020, 1220, 1250, 1270, 1320, 1420, 1520, 1580, 1620
Bitumen Size	
0.63	876, 896, 1120, 1225
Barrel Size	
0.9	914, 920, 1320
1, 1.2, 1.25	914, 920, 1225, 1320, 1580

**Note :** 914 width in barrel thickness may be available as dimension out of barrel production

width up to 1020 mm) and 600 mm (for other sizes) and Coil weight: 6-23 tonnes (as per size)

**Tolerance** as per IS - 513/1994

**Sizes of CR Plate**

Thickness (mm)	Width (mm)
0.35, 0.4, 0.5	900
0.63, 0.8	900/1000/1020
1.0, 1.25, 1.6, 1.85	900/1000/1020, 1250/1270